NC24603

generating a reminder from user input and storing said reminder in the system, the reminder for reminding at least one person of a future event to occur subsequent to a triggering event;

defining said triggering event and storing an indication of said triggering event in the system; wherein said triggering event is an event initiated external to the communication device, the indication of said triggering event and said reminder indexed together, once stored, in the system;

defining an action and storing an indication of said action in the system, said action indicating said reminder to said at least one person, and said action, once stored, indexed together with said triggering event and said reminder;

detecting an occurrence of said triggering event; and performing, in response to detecting said triggering event, said action indicating said reminder to said at least one person, at the communication device.

14. (Twice Amended) An apparatus for generating a reminder in a communication device or operating in a system, said apparatus comprising:

an input device for receiving an input in the communication device, said input generating a reminder, said reminder for reminding at least one person of a future event to occur subsequent to a triggering event, defining said triggering event, said triggering event to be initiated external to the communication device, and defining an action, wherein said action indicates said reminder to said at least one person upon occurrence of said triggering event;



NC24603

2003

at least one memory, said memory for storing said reminder, an indication of said triggering event, and an indication of said action in the system, indexed there together; and

a processor in the communication device, coupled to said input device and operable to communicate with said at least one memory, said processor for detecting occurrence of said triggering event and initiating, in response to detecting said triggering event, performance of said action indicating said reminder to said at least one person in the communication device.